

[Close Window](#)

SPL-R Series				
Specifications	SPL-800R	SPL-1000R	SPL-1200R	SPL-1500R
Drivers:	8" forward firing (6.5" piston diameter) Die-cast aluminum basket	10" forward firing (8" piston diameter) Die-cast aluminum basket	12" forward firing (9.7" piston diameter) Die-cast aluminum basket	15" forward firing (12.7" piston diameter) Die-cast aluminum basket
"ERS" Class "D" Amplifier:	2000 watts Dynamic 1000 watts RMS Power	2000 watts Dynamic 1000 watts RMS Power	2000 watts Dynamic 1000 watts RMS Power	2000 watts Dynamic 1000 watts RMS Power
IR Remote Control:	Yes	Yes	Yes	Yes
Digital Auto Room Bass EQ:	Yes	Yes	Yes	Yes
Frequency Response:	28 - 120 Hz +/- 3 dB	24 - 120 Hz +/- 3 dB	22 - 120 Hz +/- 3 dB	20 - 120 Hz +/- 3 dB
Digital Dynamic Driver Control with Current-Sensing Servo:	Yes	Yes	Yes	Yes
Digital Presets:	Movies; R&B-Rock; Jazz-Classical; Games	Movies; R&B-Rock; Jazz-Classical; Games	Movies; R&B-Rock; Jazz-Classical; Games	Movies; R&B-Rock; Jazz-Classical; Games
Digital Phase:	0, 90, 180, 270 degrees	0, 90, 180, 270 degrees	0, 90, 180, 270 degrees	0, 90, 180, 270 degrees
High Pass Crossover:	80Hz (6 dB/octave slope)	80Hz (6 dB/octave slope)	80Hz (6 dB/octave slope)	80Hz (6 dB/octave slope)
Low Pass Crossover:	40 Hz-120 Hz (adjustable) (12 dB octave, 24 dB ultimate)	40 Hz-120 Hz (adjustable) (12 dB octave, 24 dB ultimate)	40 Hz-120 Hz (adjustable) (12 dB octave, 24 dB ultimate)	40 Hz-120 Hz (adjustable) (12 dB octave, 24 dB ultimate)
Auto On/Off:	Yes	Yes	Yes	Yes
Magnet Structure:	204 oz. (12.7 lbs)	346 oz. (21.6 lbs.)	346 oz. (21.6 lbs.)	346 oz (21.6 lbs)
Voice Coil:	2.5" inside/outside voice coil	3" inside/outside voice coil	3" inside/outside voice coil	3" inside/outside voice coil
Inputs:	Gold plated line-level and speaker-level	Gold plated line-level and speaker-level	Gold plated line-level and speaker-level	Gold plated line-level and speaker-level
Outputs:	Line-level 80Hz up	Line-level 80Hz up	Line-level 80Hz up	Line-level 80Hz up
Crossover Bypass:	Subwoofer Direct	Subwoofer Direct	Subwoofer Direct	Subwoofer Direct
Cone:	Kevlar-reinforced Resin	Kevlar-reinforced Resin	Kevlar-reinforced Resin	Kevlar-reinforced Resin
Dimensions (H/W/D): (inc. feet, grill and knobs)	10.125" x 10.375" x 12.813" (27 x 26 x 33 cm) sealed	12.313" x 12.375" x 13.875" (32 x 31 x 36 cm) sealed	14.25" x 14.375" x 16.5" (37 x 36 x 41 cm) sealed	18.375" x 18" x 17.375" (47 x 46 x 44 cm) sealed

Weight (approx.):	33 lbs. (15 Kg)	46 lbs. (21 Kg)	53 lbs. (24 Kg)	65 lbs (30 Kg)
Included Accessories:	Full feature remote control, calibrated microphone, mic stand and mic cable	Full feature remote control, calibrated microphone, mic stand and mic cable	Full feature remote control, calibrated microphone, mic stand and mic cable	Full feature remote control, calibrated microphone, mic stand and mic cable
Warranty:	2 years (parts/labor)	2 years (parts/labor)	2 years (parts/labor)	2 years (parts/labor)
Finishes:	Black Gloss, Cherry or Maple	Black Gloss, Cherry or Maple	Black Gloss, Cherry or Maple	Black Pica or Cherry

Close Window