

## cremona subwoofer M

Cremona subwoofer M è un sistema di riferimento attivo per le basse frequenze, capace di produrre elevate pressioni nei toni gravi ed in grado di soddisfare tutti coloro che cercano punch, impatto ed immanenza, nella riproduzione dei loro programmi preferiti, siano essi stereofonici o in multicanale.

The Cremona Subwoofer M is an active subwoofer system designed for the proper reproduction of the lowest frequency ranges in both stereophonic and multichannel sound systems. It exhibits an exceptional capacity for low frequency extension, impact punch and dynamic output.

**FINISH:**

Black piano mat.

**DIMENSIONS:**

480 x 490 x 480 mm (HxWxD).

**WEIGHT:**

35.5 kg - net weight / 41.5 kg - shipping weight.

**SYSTEM:**

Active subwoofer with two passive radiators.

**CABINET:**

HDF construction.

**WOOFERS:**

300 mm hard paper cone, magnetically shielded, 300 mm passive radiator.

**PREAMPLIFIER:**

Selectable RCA sockets or hi-power binding posts inputs. Low-pass Linkwitz filter, 24 dB per octave. Switchable low-pass filter from 50 to 80 Hz - 6 positions. High-pass filter 19 Hz, soft start. Phase reverse switch. 3 stage limiter to avoid damages.

**AMPLIFIER:**

400 watt into 4 ohm digital amplifier. Overcurrent, low voltage, DC and thermal protections.

**POWER SUPPLY:**

14.000 uF toroidal transformer. 115 V / 230 V internally selectable.

